

Draht Binder OHG

Steinhof 31

40699 Erkrath



Stock Dimension Profile Edgings

Outer dimension	Slot width	Wall thickness	Material	Length	Wire strength	Weight/m	Wire diameter	Purpose of use
30x30	4	1.5	1.4301	3 m	4	1.5 kg	1.5 mm	Spot welded wire meshes
30x30	5.7	1.5	1.4301	3 m	3	1.5 kg	1.5 mm	Double crimp screens / flat top screens
30x30	4	1.5	blank	3 m	4	1.5 kg	1.5 mm	Spot welded wire meshes
30x30	4	1.5	blank	6 m	4	1.5 kg	1.5 mm	Spot welded wire meshes
30x30	5.7	1.5	blank	3 m	3	1.5 kg	1.5 mm	Double crimp screens / flat top screens
30x30	5.7	1.5	blank	6 m	3	1.5 kg	1.5 mm	Double crimp screens / flat top screens
30x30	7.5	1.5	blank	3 m	4	1.5 kg	1.5 mm	Double crimp screens / flat top screens
30x30	7.5	1.5	blank	6 m	4	1.5 kg	1.5 mm	Double crimp screens / flat top screens
40x40	7.5	2	blank	3 m	4	2.5 kg	2.0 mm	Double crimp

								screens / flat top screens
40x40	7.5	2	blank	6 m	4	2.5 kg	2.0 mm	Double crimp screens / flat top screens
30x30	5.7	1.5	send. galv.	3 m	3	1.5 kg	1.5 mm	Double crimp screens / flat top screens
30x30	5.7	1.5	send. galv.	6 m	3	1.5 kg	1.5 mm	Double crimp screens / flat top screens
30x30	7.5	1.5	send. galv.	3 m	4	1.5 kg	1.5 mm	Double crimp screens / flat top screens
30x30	5.7	1.5	send. galv.	6 m	4	1.5 kg	1.5 mm	Double crimp screens / flat top screens

Deviant edging profiles can be delivered on inquiry.

Contact person: Walter Günther

Email: w.guenther@draht-binder.de

Phone: 0211-280736-12